

CURVIA 3 SEAL

RING

PENDANT - RECESSED - SURFACE

 **Lumenwerx**

Declare.



Our extensive Curvia family illuminates with elegant curvilinear shapes and patterns, enhancing spaces with a soft touch and a graceful sense of movement. Curvia Seal luminaires are specifically engineered for applications that require varying levels of protection from dust and water and available at two Ingress Protection (IP) levels: IP54 and IP65.



SENSORS
For latest information on sensors, click [here](#).




Curvia Additions Brochure

Curvia Family (Refer to other spec sheets)


Curvia Mini
1"



Curvia Prism
2"




Curvia
2", 3", 4"



Curvia XYZ
2", 3"



Curvia Horizon
2", 3"




Curvia Perimeter
2", 3", 4", 5"




Curvia Seal Perimeter
2", 3", 4"



Curvia Seal
2", 3", 4"



Curvia Acoustix
2"



3737 Cote Vertu St-Laurent, Quebec, Canada H4R 2C9
T (514) 225-4304 F (514) 931-4862
www.lumenwerx.com



Lumenwerx reserves the right to modify product specifications without notification.
© Lumenwerx, ULC. All rights reserved.
CURVIA3SEAL-RING-SPEC-REVO November 15, 2024

CURVIA 3 SEAL

RING

PENDANT - RECESSED - SURFACE



IMPORTANT:
Fixture must
be installed
with lens
facing down.

Project: _____
Type: _____

Order Guide

LUMINAIRE ID	DISTRIBUTION	ENVIRONMENT ¹	SIZE ²	OPTIC
	D			EPDO
CURV3SEALRIP - Curvia 3" Seal Ring Pendant CURV3SEALRIR - Curvia 3" Seal Ring Recessed CURV3SEALRIS - Curvia 3" Seal Ring Surface	D - Direct	IP65 - IP65-Rated IP54 - IP54-Rated ¹ See page 4 for more information on the features and installation details for each environment option.	2FT - Ø 2' 3FT - Ø 3' 4FT - Ø 4' 5FT - Ø 5' 6FT - Ø 6' ² Ø 8' and over will be shipped in separate pieces. ³ Minimum Ø 2'.	EPDO - Environmentally Protected Direct Optic

LIGHT SOURCE ⁴	CRI	LUMEN PACKAGE ⁷	COLOR TEMPERATURE	VOLTAGE
SW - Static white FS - Full spectrum ⁴ Chromawerx SOLA, DUO, and QUADRO also available. Consult factory.	80CRI ⁵ - 80 CRI 90CRI ⁵ - 90 CRI 95CRI ⁶ - 95 CRI ⁵ Not available with full spectrum. ⁶ Not available with static white.	350LMF - Eco low output 350 lm/ft 500LMF - Low output 500 lm/ft 750LMF - Medium output 750 lm/ft 1000LMF ⁸ - High output 1000 lm/ft ⁷ To calculate the total lumens, multiply the lumen package (lm/ft) by the circumference of the ring (diameter x π). ⁸ Not available with full spectrum.	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K 50K - 5000K	120V - 120V 277V - 277V UNV - 120V-277V 347V ⁹ - 347V ⁹ Available with D1 driver only. Minimum Ø 5' fixture for integral drivers.

DRIVER ^{10, 11}	ELECTRICAL
D1 - 1% 0-10V ELV ^{12, 13} - ELV 120V TRI ^{12, 13} - TRIAC 120V DA ¹⁴ - DALI LDE1 ^{13, 14} - Lutron Hi-Lume 1% Eco ELD1 - eldoLED 1% ECOdrive 0-10V ELDO - eldoLED 0.1% SOLOdrive 0-10V RLTD10 ¹⁵ - Low-temperature 10% 0-10V ¹⁰ Integral or remote drivers subject to factory evaluation. ¹¹ Minimum Ø 5' fixture for integral drivers. ¹² Available with 120V only. ¹³ Not suitable for temperatures below 0°C (32°F). ¹⁴ On-site commissioning is required. ¹⁵ Remote driver box required. Suitable for temperatures down to -40°C/F.	1C - 1 circuit EC - Emergency-powered fixture NL - Night light fixture DL - Daylight fixture GTD ^{16, 17, 18} - Generator transfer device fixture +EMB ^{16, 17, 18, 19} - Emergency battery ¹⁶ Integral or remote subject to factory evaluation. GTD/EMB must be housed with the driver. ¹⁷ Not available with 347V. ¹⁸ Not suitable for environments below 0°C (32°F). ¹⁹ Not available with EC or GTD. To specify, add +EMB to the selected electrical option, e.g. 1C+EMB.

POWER FEED	MOUNTING ²¹	FINISH	OPTIONS
TF - Top feed EF ²⁰ - End feed ²⁰ Not available with pendant mounting.	PENDANT ²² STS - Stem, standard STC(J) - Stem, custom ²¹ The mounting options selected must reflect the luminaire ID. ²² Standard canopies are black for black fixtures, and white for all other finishes. See page 3 for full details on standard and custom options.	RECESSED MTR - Trim DMF - Drywall mud flange SURFACE GSM - Gasketed surface mount	W - Matte white AL - Aluminum B - Matte black WA - White antimicrobial Silverwerx CF# - Custom finish, specify RAL# CRF - Corrosion resistant finish NA - None

CURVIA 3 SEAL

RING

PENDANT - RECESSED - SURFACE



Pendant Mounting Code

Stem

Standard


STS - Stem, standard
<ul style="list-style-type: none">• Ø 5" for power canopy• Ø 5" for non-power canopy• Canopies are black for black fixtures, and white for all other fixture finishes• Stem finish is the same color as fixture• Stem length is 18"• Stem is not field adjustable

Custom

Example: STC(5NPC-36IN-W-STW-SLS)

STC() - Stem, custom				
NON-POWER CANOPY SIZE	STEM LENGTH	CANOPY FINISH	STEM COLOR	OPTIONS
5NPC - Ø 5" non-power canopy	18IN - 18" 36IN - 36" #IN ² - Specify length in inches <small>² Minimum length is 6". Maximum length is 72". Stem is not field adjustable.</small>	W - Matte white AL - Aluminum B - Matte black CF# - Custom finish, specify RAL#	STW - Matte white STAL - Aluminum STB - Matte black STCF# - Custom finish, specify RAL#	SLS - Sloped ceiling for stem NA - None

Dimensions



CURVIA 3 SEAL

RING

PENDANT - RECESSED - SURFACE



Environment Options

DIRECT


IP65-RATED




Fixture is dust-tight and sealed against water jets from any direction.

Wet listed

Low-profile joiner bridge every 8'



Direct




OUTDOOR: Exposed to the elements

Suitable for ambient temperatures of -20°C (-4°F) to 30°C (86°F) **

INDOOR: Wet Listed applications, healthcare applications, high-maintenance settings


IP54-RATED




Fixture is dust and water-splash protected with reinforced sealed protection for internal electrical components*. The lens, joiners and end caps are gasketed for secure sealing.

Wet listed

Gasketed joiner



Direct



OUTDOOR: Mild exposure to the elements, under canopy

Suitable for ambient temperatures of -20°C (-4°F) to 30°C (86°F)**

INDOOR: Wipe-down environments

* Internal electrical components are IP65-rated. The driver is fully enclosed, wiring connections are sealed to prevent ingress of dust and moisture, and the LED board is conformal-coated for enhanced protection.

** Some restrictions apply.

CURVIA 3 SEAL

RING


PENDANT - RECESSED - SURFACE



Photometrics

Values calculated based on Curvia 3 Ring Ø 2' at 3500K and 80 CRI.

DIRECT OPTIC



MULTIPLIER TABLES

Use these tables to get results for different color temperatures and CRI.

Multiplier - CCT/CRI

CCT	WATTS		LPW	
	80 CRI	90 CRI	80 CRI	90 CRI
2700K	1.05	1.27	0.95	0.79
3000K	1.02	1.23	0.98	0.81
3500K	1.00	1.19	1.00	0.84
4000K	1.00	1.19	1.00	0.84
5000K	0.96	1.12	1.04	0.89



CURVIA 3 SEAL

RING

PENDANT - RECESSED - SURFACE



Technical Specifications

OPTICS

Environmentally Protected Optic (EPDO)

The Environmentally Protected Optic features an innovative sealed design with our exclusive Supreme Grip™ Technology and advanced gasketing, ensuring a precise, secure fit on the extrusion while delivering superior protection against dust, water, and UV distortion.

LIGHT SOURCE

Static white

Custom array of mid-flux LEDs are cartridge-mounted with quick-connect wiring to facilitate service and thermal management. Available in 2700K, 3000K, 3500K, 4000K, and 5000K with a minimum 80 CRI and an option for 90 CRI with elevated R9 value. Color consistency maintained to within 3 SDCM. LEDs operate at reduced drive current to optimize efficacy and lumen maintenance. All LEDs have been tested in accordance with IESNA LM-80-08 and the results have shown L80 lumen maintenance greater than 60,000 hours. Absolute product photometry is measured and presented in accordance with IESNA LM-79, unless otherwise indicated.

Full spectrum

The full spectrum LED option offers improved color particularly in the cyan region that is beneficial in both healthcare and circadian lighting strategies. The cyan region in full spectrum LED is richer at the 480 nm range.

ELECTRICAL

Factory-set, adjustable output current LED driver with universal (120-277 VAC) input. Dimmable from 100% to 1% with 0-10V dimming control. Rated life (90% survivorship) of 50,000 hours at 50°C max. ambient (and 70°C max. case) temperature. At maximum driver load: Efficiency>84%, PF>0.9, THD<20%. Other specifiable options include Lutron Hi-Lume 1% Eco, eldoLED 1% ECOdrive 0-10V, eldoLED 0.1% SOLOdrive 0-10V, ELV, TRIAC, and DALI protocol drivers. All of our standard 0-10V drivers are NEMA 410 compliant. An optional low temperature 10% 0-10V driver, suitable for temperatures down to -40°C/F is also available.

PoE

Depending on the PoE manufacturer selected, Lumenwerx will install the node in factory as either integral to the luminaire or as a remote module. Factory programming of the PoE node may or may not enable the following functionalities: lumen package, DUO (tunable white), QUADRO (RGBW), emergency battery backup, and sensor integration. These must be addressed and evaluated on a case-by-case basis.

Battery

Factory installed long life, high temperature, maintenance-free Lithium-Ion battery pack with self-test functionality, test switch and charge indicator. Minimum of 90 minutes operation, up to 1000 lumens per 4' (25°C) emergency lighting output and recharge time of 24 hours.

Generator Transfer Device (GTD)

A UL924 listed shunt relay that can bypass both line voltage (120-277 VAC) and 0-10V dimming signal. Suited for ambient temperatures of 0°C (32°F) to 60°C (140°F).

MOUNTING

Pendant: Pendant fixtures can be mounted with stem.

Recessed: Recessed fixtures can be mounted in ceilings with trim or mud flange options.

Surface: Surface fixtures can be mounted directly to hard surface ceilings, hardware supplied by others. A minimum of 6" from the vertical wall is required.

FINISH

Interior: 95%, reflective matte powder coated white paint.

Exterior: Matte white, matte black or aluminum powder coating. Custom finishes are also available.

CONSTRUCTION

Housing: Extruded aluminum and aluminum sheet, up to 90% recycled content

Reflectors: Aluminum

Lens: Polycarbonate

Stem: Ø 1/2" threaded steel tube

WEIGHT

	Pendant	Recessed	Surface
IP65	2.5 lb/ft - 1.13 kg/ft	3 lb/ft - 1.36 kg/ft	2.5 lb/ft - 1.13 kg/ft
IP54	2.25 lb/ft - 1.02 kg/ft	2.8 lb/ft - 1.27 kg/ft	2.25 lb/ft - 1.02 kg/ft

CERTIFICATIONS

ETL: IP65 environment option is IP65 rated. WET environment option is rated for dry/damp locations. WETL environment option is ETL Wet Listed. Conforms to UL Standard 1598 and certified to CAN/CSA Standard C22.2 No. 250.0. During the installation of WETL and IP65 fixtures, the contractor is responsible for properly sealing all mounting and electrical connection points.

IC rated: Suitable for direct contact with insulation. For Recessed mounting only.

CURVIA 3 SEAL

RING

PENDANT - RECESSED - SURFACE



WARRANTY

Lumenwerx provides a five-year limited warranty on electrical and mechanical performance of the luminaires, including the LED boards, drivers, and auxiliary electronics. Lumenwerx will repair or replace defective luminaires or components at our discretion, provided they have been installed and operated in accordance with our specifications. Other limitations apply, please refer to the full warranty on our website.