

GLOBE

PENDANT

Lumenwerx



Globe is a fully illuminated sphere designed to deliver balanced illumination within architectural spaces. Crafted from high-quality frosted glass, its internal optic ensures smooth, even light distribution in all directions, providing visual comfort without glare or hotspots. Available in a range of diameters and mounting options, Globe can be used as an individual luminaire with strong visual presence or deployed in larger architectural arrangements.



Globe Brochure



Pivot Globe
Module

Light Source

Static White

SOLA

DUO



Project: _____

Type: _____

Order Guide - Static White

For SOLA Dim-to-Warm and DUO Tunable White order guide, see page 3

LUMINAIRE ID	SIZE	OPTIC	LIGHT SOURCE	CRI
GLBP		IRO		
GLBP - Globe Pendant	4IN - Ø 4" 6IN - Ø 6" 8IN - Ø 8" 12IN - Ø 12" 16IN - Ø 16"	IRO - Isotropic Radiant Optic	SW - Static white FS - Full spectrum static white	<u>Static white</u> 80CRI - 80+ CRI 90CRI - 90+ CRI 95CRI - 95+ CRI <u>Full spectrum</u> 95CRI - 95+ CRI

LUMEN PACKAGE	COLOR TEMPERATURE	VOLTAGE	DIMMING	
Ø 4"	525LM - 525 lm	22K ¹ - 2200K 24K ² - 2400K 27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K 50K ² - 5000K	120V - 120V 277V - 277V UNV - 120V-277V 347V ³ - 347V	CANOPY DRIVER D1 - 1% 0-10V ELV ⁴ - ELV 120V TRI ⁴ - TRIAC 120V DA ^{5,6,7} - DALI ELD1 ^{6,7} - eldoLED 1% ECodrive 0-10V ELDO ^{6,7} - eldoLED 0.1% SOLOdrive 0-10V
Ø 6"	800LM - 800 lm			REMOTE DRIVER ⁸ RD1 - 1% 0-10V RELV ⁴ - ELV 120V RTRI ⁴ - TRIAC 120V RDA ⁵ - DALI RLED1 ⁵ - Lutron Hi-lume 1% Eco RELD1 - eldoLED 1% ECodrive 0-10V RELD0 - eldoLED 0.1% SOLOdrive 0-10V +EB ^{9,10} - Emergency battery
Ø 8"	1200LM - 1200 lm			
Ø 12"	1900LM - 1900 lm			
Ø 16"	2300LM - 2300 lm	¹ Only available with 90+ CRI. ² Not available with 95+ CRI.	³ Only available with RD1 driver. Please consult factory.	⁴ Only available with 120V. ⁵ On-site commissioning is required. ⁶ Only available with DR canopy option. ⁷ Not available with Ø 16". ⁸ A remote driver box is provided. ⁹ To specify, add +EB to the selected dimming option, e.g. RD1+EB. ¹⁰ Not available with Ø 4".

ELECTRICAL	CANOPY TYPE ¹¹	CANOPY FINISH	SUSPENSION	
1C				
1C - 1 circuit	FLR ¹² - Flat round canopy, 4" octagonal junction box CDR ¹² - Conduit feed, round canopy DMNC ¹³ - Direct mount, new construction DMRM ^{13,14} - Direct mount, remodel DR - Deep round canopy	FTMB - Matte black FTMW - Matte white CF# ¹⁵ - Custom finish, specify RAL#	POWER CORD ¹⁶ BPC##IN - Black PVC WPC##IN - White PVC	STEM ¹⁷ BKS##IN - Matte black stem WHS##IN - Matte white stem BKSS##IN ¹⁸ - Matte black swivel stem WHSS##IN ¹⁸ - Matte white swivel stem CF#S##IN ¹⁹ - Custom finish stem CF#SS##IN ^{18,19} - Custom finish swivel stem

¹¹ See page 5 for details.
¹² Ø 16" requires a remote driver.
¹³ Only available with remote driver.
¹⁴ Single wiring entry only. No daisy chain connections allowed.

¹⁵ See page 7 for more finish options.

¹⁶ Min 18" - max 72", specify length (##) in inches.

¹⁷ Min 10" - max 72", specify length (##) in inches.
¹⁸ Not available with DMNC, DMRM and DR canopy options.
¹⁹ Specify RAL#.



Project: _____

Type: _____

Order Guide - SOLA Dim-to-Warm and DUO Tunable White

For static white order guide, see page 2

LUMINAIRE ID	SIZE	OPTIC	LIGHT SOURCE	CRI
GLBP		IRO		90CRI
GLBP - Globe Pendant	4IN - Ø 4" 6IN - Ø 6" 8IN - Ø 8" 12IN - Ø 12" 16IN - Ø 16"	IRO - Isotropic Radiant Optic	SOLA - Dim-to-warm single channel control DUO - Tunable white 2-channel control	90CRI - 90+ CRI

LUMEN PACKAGE		COLOR TEMPERATURE	VOLTAGE	DIMMING
Ø 4"	215LM - 215 lm	SOLA 30K18K - 3000K to 1800K 27K18K - 2700K to 1800K	120V - 120V 277V - 277V UNV - 120V-277V	REMOTE DRIVER ¹ SOLA ² RSD1 - Single 0-10V input
Ø 6"	685LM - 685 lm			DUO RDMX ³ - DMX RDDA ³ - DALI DT6 RDDA8 ³ - DALI DT8 RDD1 - Dual 0-10V input for CCT/intensity RLD2 ³ - Lutron DALI-2 digital +EB ^{4,5} - Emergency battery
Ø 8"	800LM - 800 lm	DUO		
Ø 12"	975LM - 975 lm	65K27K - 6500K to 2700K 50K27K - 5000K to 2700K		
Ø 16"	1650LM - 1650 lm			

¹A remote driver box is provided.

²Consult factory for ELV/TRIAC.

³On-site commissioning is required.

⁴To specify, add +EB to the selected dimming option, e.g. RDD1+EB.

⁵Not available with Ø 4".


ELECTRICAL	CANOPY TYPE ⁶	CANOPY FINISH	SUSPENSION	
1C				
1C - 1 circuit	FLR - Flat round canopy, 4" octagonal junction box CDR - Conduit feed, round canopy DMNC - Direct mount, new construction DMRM ⁷ - Direct mount, remodel DR - Deep round canopy ⁶ See page 5 for details. ⁷ Single wiring entry only. No daisy chain connections allowed.	FTMB - Matte black FTMW - Matte white CF# ⁸ - Custom finish, specify RAL#	POWER CORD ⁹ BPC##IN - Black PVC WPC##IN - White PVC ⁸ See page 7 for more finish options.	STEM ¹⁰ BKS##IN - Matte black stem WHS##IN - Matte white stem BKSS##IN ¹¹ - Matte black swivel stem WHSS##IN ¹¹ - Matte white swivel stem CF#S##IN ¹² - Custom finish stem CF#SS##IN ^{11,12} - Custom finish swivel stem

¹⁰Min 10" - max 72", specify length (##) in inches.




¹¹Not available with DMNC, DMRM, and DR canopy options.





¹²Specify RAL#.

Dimensions






Mounting

CANOPY DRIVER			
Order code	FLR Flat round canopy, 4" octagonal junction box	CDR Conduit feed, round canopy	DR Deep round canopy
Canopy type			
Canopy size	Ø 4 1/2" Height 3/8"	Ø 5 1/2" Height 115/16"	Ø 5 5/8" Height 13/8"
Suspension	Power cord, Stem, Swivel stem		Power cord, Stem


REMOTE DRIVER				
Order code	FLR Flat round canopy, 4" octagonal junction box	CDR Conduit feed, round canopy	DMNC Direct mount, new construction	DMRM Direct mount, remodel
Canopy type				
Canopy size	Ø 4 1/2" Height 3/8"	Ø 5 1/2" Height 115/16"	Ø 3 1/8" Height 2"	Ø 5 5/8" Height 13/8"
Suspension	Power cord, Stem, Swivel stem		Power cord, Stem	Single wiring entry only. No daisy chain connections allowed.

Suspension

POWER CORD		STEM	
PVC		Stem	Swivel stem ^{1,2}
			
Power Cord Lengths (*)		Stem Lengths (*)	
Min 18" Max 72"		Min 10" Max 72" Max 45° tilt	

¹Not available with DMNC, DMRM, and DR canopy options.
²The total stem length (*) includes the 1" swivel base located inside the canopy.

Photometrics



Static white

Values calculated based on 3500K.

SIZE	LM	W	LM/W
Ø 4"	525	10	53
Ø 6"	800	12	67
Ø 8"	1200	14	86
Ø 12"	1900	22	86
Ø 16"	2300	28	82

SOLA / DUO

Values calculated at high end CCT.

SIZE	LM	W	LM/W
Ø 4"	215	8	27
Ø 6"	685	14	49
Ø 8"	800	14	57
Ø 12"	975	16	61
Ø 16"	1650	28	59

MULTIPLIERS

Use this table to get results for different color temperatures.

CCT	
2200K	0.80
2400K	0.87
2700K	0.94
3000K	0.98
3500K	1
4000K	1.05
5000K	1.05

Finishes

Standard



FTMW - Matte White




FTMB - Matte Black

Custom

Neutrals



CRM - Cream



GRY - Gray



STG - Steel Gray



SAG - Sage Gray



BLB - Black Blue


Designer



ALM - Almond




RST - Rust Fine Texture



GRB - Green Beige



YLW - Yellow



SLM - Salmon Pink



VIO - Pastel Violet



RED - Red



PRR - Purple Red



SMB - Storm Blue




DPB - Deep Blue



OCB - Ocean Blue



BLG - Blue Green



GNS - Green Smoke



MNG - Mint Green

Metallics



CHP - Champagne



DBZ - Dark Bronze




CNY - Canyon

Premium Custom

Neutrals



MOG - Moss Gray



QRZ - Quartzite Texture



LMG - Lime Green



GLD - Gold



IRN - Iron Ore



SBP - Sandblast Copper



SWD - Sandalwood

Some colors may have longer lead time.

Technical Specifications

OPTIC

Isotropic Radiant Optic™ (IRO™)

The Isotropic Radiant Optic™ (IRO™) is a spherical lens designed with a spike-textured surface through which light rays are diffused outward and equally in all directions.

LIGHT SOURCE

Static white

Compact COB (Chip-On-Board) LED module, available in 2200K, 2400K, 2700K, 3000K, 3500K, 4000K, and 5000K with a choice of 80+ CRI, 90+ CRI, or 95+ CRI, with an elevated R9 value for 90+ CRI and above. Color consistency is maintained to within 2 SDCM. All LEDs have been tested in accordance with IESNA LM-80-08 and the results have shown L80 lumen maintenance greater than 60,000 hours. Absolute product photometry is measured and presented in accordance with IESNA LM-79, unless otherwise indicated.

Full spectrum static white

The full spectrum LED option offers improved color particularly in the cyan region that is beneficial in both healthcare and circadian lighting strategies. The cyan region in full spectrum LED is richer at the 480 nm range.

Chromawerx SOLA

Chromawerx SOLA is single-channel control that dims output while warming the color temperature in a pre-determined relationship. Two color temperature range options are offered: 3000K to 1800K, and 2700K to 1800K. A simple analog control adjusts a specially populated LED array to emulate the effect of dimming a filament source.

Chromawerx DUO

Chromawerx DUO offers a two-channel control system which uses analog or digital protocols for synchronous control of both cool to warm LED arrays - maintaining a CRI above 90. Two color temperature range options are offered: 6500K to 2700K, and 5000K to 2700K. The range of color DUO offers is useful for entraining circadian rhythms, stimulating alertness, and compensating for jet lag among other applications. The Chromawerx drivers are programmed to limit maximum light output and power usage across all color temperatures. When paired with DALI drivers (DDA/DDA8), color tuning follows a linear dimming curve.

ELECTRICAL

Unless otherwise specified, dimming down to 1%. At maximum driver load: efficiency>84%, PF>0.9, THD<20%. ELV and TRIAC dimming performance (including minimum dimming percentage) subject to dimmer selection.

Canopy driver: 1% 0-10V, ELV, TRIAC, DALI, eldoLED 1% ECODrive 0-10V, eldoLED 0.1% SOLO drive 0-10V

Remote driver: 1% 0-10V, ELV, TRIAC, DALI, Lutron Hi-Lume 1% Eco, eldoLED 1% ECODrive 0-10V, eldoLED 0.1% SOLOdrive 0-10V, DMX, Lutron DALI-2 digital

Emergency battery option: Remotely-installed, long-life, high-temperature, maintenance-free, Bodine Lithium-Ion battery pack with self-test functionality, test switch and charge indicator. IOTA and Fulham options available upon request. Minimum of 90 minutes operation, and recharge time of 24 hours. For fixtures less than 10 W, the battery provides 6 W of emergency light output. For fixtures 10 W and over, the battery provides 10 W.

PoE

Depending on the PoE manufacturer selected, Lumenwerx will install the node in factory as either integral to the luminaire or as a remote module. Factory programming of the PoE node may or may not enable the following functionalities: lumen package, DUO (tunable white), QUADRO (RGBW), emergency battery backup, and sensor integration. These must be addressed and evaluated on a case-by-case basis.

FINISH

Standard powder-coat paint available in matte white and black. Custom colors are also available.

CONSTRUCTION

Globe: Frosted glass

Power cord: Black and white PVC, 18" to 72" standard length

Stem: Ø 1/2" rigid stem and swivel stem 10" to 72" standard length

Canopy: Flat, conduit feed, direct, and deep

WEIGHT

Ø 4": 1.10 lbs - 0.5 kg

Ø 6": 1.76 lbs - 0.8 kg

Ø 8": 2.65 lbs - 1.2 kg

Ø 12": 6.83 lbs - 3.1 kg

Ø 16": 11.90 lbs - 5.4 kg

CERTIFICATION

ETL: Rated for indoor dry/damp locations. Conforms to UL Standard 1598 and certified to CAN/CSA Standard C22.2 No. 250.0.

WARRANTY

Lumenwerx provides a five-year limited warranty on electrical and mechanical performance of the luminaires, including the LED boards, drivers, and auxiliary electronics. Lumenwerx will repair or replace defective luminaires or components at our discretion, provided they have been installed and operated in accordance with our specifications. Other limitations apply, please refer to the full warranty on our website.