

MIKRO LED

RECESSED VERTICAL



LUMENWERX
WWW.LUMENWERX.COM

ONLY 1 INCH WIDE



INTEGRATED™
MIKRODRIVE

DESCRIPTION

Precise, refined, elegant, and just 1" wide, Mikro presents a crisp, brand new scale in linear LED luminaires, made practical by an integral driver - **Mikrodrive™**. Using a high performance LEDs and a flat, high-efficiency lambertian optic, Mikro delivers an efficacy of 95 LPW. In addition to patterns with fully lighted corners and a wide range of ceiling trim details, Mikro is also available in pendant, wall, and surface configurations (see separate specification sheets).

PROJECT: _____

TYPE: _____

NOTES: _____

ORDER GUIDE


IC RATED

MIKRV	HLO	LED			
LUMINAIRE ID	OPTICS	LIGHT SOURCE	CRI	LUMEN PACKAGES	COLOR TEMP.
MIKRV - Mikro Recessed vertical	HLO - High-efficiency Lambertian Optic	LED - high performance LED	80 - 80CRI 90 - 90CRI	350 - min. low output 350lm/ft 500 - max. medium output 500lm/ft #### - other required lm/ft	27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K

LUMINAIRE LENGTH	VOLTAGE	MIKDR	ELECTRICAL	MOUNTING	FINISH	OPTIONS
Standard sections - 4', 8' & 12' For all other specify length #FT#IN - Specify nominal length (#) in 1' and/or 1" increments Continuous Run - for luminaires over 12' Minimum individual section 4'	120 - 120V 277 - 277V UNV - 120V-277V	MIKDR - 0-10V mikro driver	1 - 1 circuit +EM* - emergency light circuit * for a minimum of 4' section	DTL - drywall trimless DMF - drywall mud flange	W - matte white CF# - custom finish specify RAL#	CU - custom

See page 2 for ordering code detailed information

CROSS SECTION



MIKRV - recessed vertical

OPTICS



HLO - High-efficiency Lambertian Optic



OPTICS

HIGH EFFICIENCY LAMBERTIAN OPTIC (HLO) - matte white side reflectors combined with High-efficiency Lambertian Optic (HLO) shielding of diffusing 0.075" thick acrylic and good source obscuration. Luminaire brightness is controlled by the flux-to-shielding area ratio.

LIGHT SOURCE - LED

Custom linear array of mid-flux LEDs are cartridge-mounted with quick-connect wiring to facilitate service and thermal management. Available in 2700K, 3000K, 3500K and 4000K with a minimum 80 CRI and an option for 90 CRI with elevated R9 value. Color consistency maintained to within 3 SDCM. LEDs operated at reduced drive current to optimize efficacy and lumen maintenance. All LEDs have been tested in accordance with IESNA LM-80-08 and the results have shown L80 lumen maintenance greater than 60,000 hours. Absolute product photometry is measured and presented in accordance with IESNA LM-79, unless otherwise indicated.


PERFORMANCE PER 4' AT 4000K

LED output	Color Temp	Watts	Nominal Delivered Lumens	Efficacy LPW
low output	4000K	14.5	1400	95
medium output	4000K	21.5	2000	94

LUMINAIRE LENGTH

Mikro is made up of standard 4, 8 and 12 foot sections that may be joined together to create longer continuous run lengths. Exact run length must be noted in the product code. The minimum individual section available is 4 foot. All individual sections are joined together onsite using the joiner kits provided. Lumenwerx offers joiner kits that are extremely simple to work with in the field and result in a fixture that appears virtually seamless with no light leak at any connection.

Joining system




ELECTRICAL - INTEGRATED DRIVER


Fully integrated, ultra-slim, **Mikrodrive™** driver eliminates the need for the remote drivers typical of very small cross-section luminaires. Factory-adjustable drive current and universal (120-277VAC) input. Long life: over 100,000 hours Mean Time Between Failures (MTBF). At maximum driver load: Efficiency > 84%, PF > 0.9, THD < 20%. Due to space limitations, other driver, control and wiring options are not currently available.

MOUNTING OPTIONS

Recessed Mounting for drywall is available with mud flange or trimless



DTL - drywall trimless



DMF - drywall mud flange

FINISH

Interior - 95%, reflective matte powder coated white paint

Exterior - matte white or aluminum powder coating. Custom finishes are also available.

CONSTRUCTION

Housing - Extruded aluminum (0.060" nominal) up to 90% Recycled content

Interior brackets - Die formed cold rolled sheet steel 20 gauge thick

Joining system - Die Formed galvanized sheet 20 gauge

Reflectors - Flat rolled Steel sheet 0.030" thick precisely die formed, 95% reflective matte white painted

Mud flange - Extruded aluminum (0.075" nominal) up to 90% Recycled content

End caps - Die cast aluminum

WEIGHT

Mikro 4ft - 3.64 lbs - 1.65 KG

Mikro 8ft - 6.36 lbs - 2.88 KG

Mikro 12ft - 9.08 lbs - 4.12KG

CERTIFICATIONS


ETL - Rated for Indoor Dry/Damp locations. Conforms to UL Standard 1598 and certified to CAN/CSA Standard C22.2 No. 250.0.

IC rated - suitable for direct contact with insulation.

WARRANTY

Lumenwerx provides a five-year limited warranty of electrical and mechanical performance of the luminaires, including the LED boards, drivers, and auxiliary electronics. Lumenwerx will repair or replace defective luminaires or components at our discretion, provided they have been installed and operated in accordance with our specifications. Other limitations apply, please refer to the full warranty on our website.


350 LUMEN AT 80CRI - LOW OUTPUT



PERFORMANCE PER 4'

LED output	Color Temp	Watts	Nominal Delivered Lumens	Efficacy LPW
low output	3000K	15.5	1400	91
low output	3500K	15	1400	92
low output	4000K	14.5	1400	95

500 LUMEN AT 80CRI - MEDIUM OUTPUT



PERFORMANCE PER 4'

LED output	Color Temp	Watts	Nominal Delivered Lumens	Efficacy LPW
medium output	3000K	22	2000	90
medium output	3500K	22	2000	91
medium output	4000K	21.5	2000	94