

**NOTE:** Wire dimming conductors as Class 1




This product must be installed in accordance with the National Electrical Code and all applicable local codes, by a person familiar with the construction and operation of the product, and the hazards involved. proper grounding is required for safety.

Ce produit doit être installé suivant le code national de l'électricité, ainsi que tous les codes locaux applicables, par une personne familière avec la construction et le fonctionnement du produit, ainsi que tous les risques qui y sont associés. la mise à terre électrique est obligatoire pour la sécurité.




Rize SW, BIOSST, BIOSDY, Full Spectrum and SOLA are non-IC rated. Do not install with insulation directly on the fixture. Rize DUO is IC rated.



1


## MASTER FIXTURE



**Warning:** A luminaire with more than one power supply connection means shall be connected to only one branch circuit.


2

## MASTER FIXTURE




Make sure the power to the fixture is turned off. Bend the tabs (A) on the end of the fixture. For a continuous system, leave tabs close. Power feeds must be brought to the master fixture.

3









Remove ceiling tiles (B) where the fixture will be installed as well as the adjacent tiles for easy access during installation.

4



Raise the fixture above the ceiling and lower the fixture (C) onto the T-bars (D).



11

Make the connection between low voltage connector (O) to the satellite fixture (M) quick connector (P). Install the BX connector (O) to the power plate (N). Reinstall the power plate (N) to the fixture (M).

Make the connection between low voltage connector (O) to the satellite fixture (M) quick connector (P).  
Install the BX connector (O) to the power plate (N).  
Reinstall the power plate (N) to the fixture (M).