















**NOTE:** Sensors listed below are not applicable to all products. Sensor suitability is project dependant, consult factory.

**Connected Controls**

 <p><b>LU - Lutron</b></p>		<p>Wireless fixture controller available with occupancy/daylight sensor or as RF-only. Controls fixtures with Lutron EcoSystem drivers or self-powered DALI drivers as part of a Lutron controls system (provided by others).</p>	<p><a href="#">Spec sheet link</a></p>
 <p><b>EN - Enlighted</b></p>		<p>Wireless sensor that can detect occupancy, daylight and provide asset tracking as part of an Enlighted controls system (provided by others).</p>	<p><a href="#">Spec sheet link</a></p>
 <p><b>ENC - Encelium</b></p>		<p>Wireless fixture controller available with occupancy/daylight sensor or as RF-only. Controls fixtures with 0-10V drivers or DEXAL drivers as part of an Encelium controls system (provided by others).</p>	<p><a href="#">Spec sheet link</a></p>
 <p><b>WL - Cooper Wavelinx</b></p>		<p>Wireless fixture controller with occupancy/daylight sensor. Controls fixtures with 0-10V drivers as part of a Wavelinx controls system (provided by others).</p>	<p><a href="#">Spec sheet link</a></p>
 <p><b>AN - Acuity nLight</b></p>		<p>Both wired (nLight Wired) and wireless (nLight Air) fixture controllers available with occupancy/daylight sensor or as RF-only. Wired load controllers are also available. Controls fixtures with 0-10V drivers or via LEDcode as part of an nLight controls system (provided by others).</p>	<p><a href="#">Spec sheet link</a></p>
 <p><b>CA - Casambi</b></p>		<p>Wireless fixture controllers, switches and other devices to control fixtures with 0-10V or DALI drivers as part of a Casambi Bluetooth controls system (provided by others).</p>	<p><a href="#">Spec sheet link</a></p>
 <p><b>LG - Legrand</b></p>		<p>Wireless fixture controller with occupancy/daylight sensor. Controls fixtures with 0-10V drivers as part of a Wattstopper DLM controls system (provided by others).</p>	<p><a href="#">Spec sheet link</a></p>

**NOTE:** Sensors listed below are not applicable to all products. Sensor suitability is project dependant, consult factory.

**Standalone Controls**

**OMS**



Standalone PIR occupancy sensor. Turns fixtures on/off according to occupancy detection, can be configured to dim to a given level (e.g. 50% of max) by request.

**ODS**



Standalone daylight photosensor. Adjusts dim levels of fixture based on ambient light.

**OCS**



Standalone occupancy + daylight sensors. Uses same sensors as OMS and ODS options to achieve both functions in the same fixture. Requires both sensors (two blank sections).

**OSS**



Standalone ultrasonic occupancy sensor. Suitable for staircase applications. Requires minimum 7" blank section.

**OWS**



Standalone wet rated (IP66) low voltage PIR occupancy sensor. Suitable for wet/outdoor installations and temperatures as low as -40 degrees C.