





RECESSED

Project:	
Type:	

### Order Guide

**IC RATED** 

LUMINAIRE ID	ОРТІС	LIGHT SOURCE	CRI	LUMEN PACKAGE	COLOR TEMP.
		sw			
SHLU3PERL - Shalo Ultra 3" Perimeter Level SHLU3PERS - Shalo Ultra 3" Perimeter Shallow SHLU3PERD - Shalo Ultra 3" Perimeter Deep	SLO - Shallow Lambertian Optic SMPO - Shallow Micro-Prismatic Optic	<b>sw</b> - Static white	80CRI - 80+ CRI 90CRI - 90+ CRI	250LMF - Hypo output 250 lm/ft 350LMF - Low output 350 lm/ft 500LMF - Medium output 500 lm/ft 750LMF - High output 750 lm/ft 1000LMF - Hyper output 1000 lm/ft	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K 50K - 5000K


LUMINAIRE LENGTH	VOLTAGE	DRIVER	ELECTRICAL
#FT#IN - Specify nominal length (#) in 1'	<b>120V</b> - 120V	<b>D1</b> - 1% O-10V	1C - 1 circuit
and/or 1" increments	<b>277∨</b> - 277∨	ELV <sup>2</sup> - ELV 120V	#MC4 - Multi circuit
	UNV - 120V-277V	TRI 2 - TRIAC 120V	EC - Emergency-powered fixture
Standard nominal lengths:	<b>347V</b> ¹- 347∨	DA 3 - DALI	NL - Night light fixture
Single units: 2' to 8'		LDE1 3 - Lutron Hi-Lume 1% Eco	DL - Daylight fixture
Continuous runs: lengths over 8'	<sup>1</sup> Available with D1 driver only.	ELD1 - eldoLED 1% ECOdrive 0-10V	GTD 5, 6 - Generator transfer device fixture
_		ELDO - eldoLED 0.1% SOLOdrive 0-10V	
			<sup>4</sup> Specify total number of circuits (#), including any required for
		<sup>2</sup> Available with 120V only.	electrical section options. Provide drawing or layout specifications.
		<sup>3</sup> On-site commissioning is required.	Minimum 4' section per circuit.
			Minimum 4' fixture.
			<sup>6</sup> Not available with 347V.

ELECTRICAL SECTIONS (optional) 7,8	MOUNTING	FINISH	OPTIONS <sup>13</sup>
#EC##9 - Emergency-powered section #NL##9 - Night light section #DL##9 - Daylight section #GTD##9,10,11 - Generator transfer device section #EMB <sup>11,12</sup> - Emergency battery NA - None  7 Specify with multi circuit (#MC) electrical option only. 8 Provide drawing or layout specifications. Consult factory for other configurations. Default section length is 4: 9 Specify quantity (#), and section length in inches (##). 10 Minimum 4' section. 11 Not available with 347V. 12 Specify quantity (#). All batteries will be on the same circuit. Each battery powers a 4' section.	TC9 - Tegular 9/16" TC15 - Tegular 15/16" TB9 - T-bar 9/16" TB15 - T-bar 15/16" ST - Screw slot T-bar MTR - Trim MTL - Trimless DMF - Drywall mud flange	W - Matte white CF# - Custom finish, specify RAL#	NEF <sup>14</sup> - No end flanges FU120 - Fuse 120V FU277 - Fuse 277V FWC - Flexible whip cable (6' std) CP - Chicago Plenum NA - None <sup>13</sup> Separate codes with a "+" if more than one is specified. <sup>14</sup> For wall-to-wall installations.


## RECESSED

### **Dimensions**


#### Level




Shallow




Deep




MTR - Trim




MTL - Trimless



DMF - Drywall mud flange



GRID



	TG9	TB9	TG15	TB15	ST
	Tegular 9/16"	T-bar 9/16"	Tegular 15/16"	T-bar 15/16"	Screw slot T-bar
A wall to flange	43	/8"	41	/2"	4 3/8"
B wall to T-bar	4 7/16"		4 9/16"		4 7/16"



RECESSED

### Photometrics

Values calculated based on a 4' fixture at 3500K and 90+ CRI for all optics.



LM/FT	W/FT	LM/W
250	2	125
350	2.9	122
500	4.2	119
750	6.4	117
1000	8.7	114



LM/FT	W/FT	LM/W
250	2	122
350	2.9	119
500	4.3	116
750	6.6	114
1000	9	111

#### MULTIPLIER TABLE

Use this table to get results for different color temperatures and CRI for all photometric tables.

Multiplier - CCT/CRI

сст	WA	TTS	LF	w
	80+ CRI	90+ CRI	80+ CRI	90+ CRI
2700K	1.05	1.27	0.95	0.79
3000K	1.02	1.23	0.98	0.81
3500K	1.00	1.19	1.00	0.84
4000K	1.00	1.19	1.00	0.84
5000K	0.96	1.12	1.04	0.89



### RECESSED

## Technical Specifications

#### **OPTICS**

#### Shallow Lambertian Optic (SLO)

A low-profile optic with diffusing acrylic that provides wide light distribution, with matte white reflectors enhancing LED output spread.

#### Shallow Micro-Prismatic Optic (SMPO)

A low-profile optic featuring a micro-prismatic lens that balances refraction and reflection, reducing glare while maintaining efficiency and uniform light distribution.

#### LIGHT SOURCE

#### Static white

Custom array of mid-flux LEDs are cartridge-mounted with quick-connect wiring to facilitate service and thermal management. Available in 2700K, 3000K, 3500K, 4000K, and 5000K with a minimum 80+ CRI and an option for 90+ CRI with elevated R9 value. Color consistency maintained to within 3 SDCM. LEDs operate at reduced drive current to optimize efficacy and lumen maintenance. All LEDs have been tested in accordance with IESNA LM-80-08 and the results have shown L80 lumen maintenance greater than 60,000 hours. Absolute product photometry is measured and presented in accordance with IESNA LM-79, unless otherwise indicated.

#### LUMINAIRE LENGTH

Shalo Ultra Perimeter is available in standard lengths of 2' to 8'. Continuous runs are available for run lengths over 8'. Exact run length must be noted in the product code. The minimum length is 2', and can be ordered in 1' and/or 1" increments. All individual sections are joined together onsite using the joiner kits provided. Lumenwerx offers joiner kits that are extremely simple to work with in the field and result in a fixture that appears virtually seamless with no light leak at any connection.

#### ELECTRICAL

Factory-set, adjustable output current LED driver with universal (120-277 VAC) input. Dimmable from 100% to 1% with 0-10V dimming control. Rated life (90% survivorship) of 50,000 hours at 50°C max. ambient (and 70°C max. case) temperature. At maximum driver load: Efficiency>84%, PF>0.9, THD<20%. Other specifiable options include Lutron Hi-Lume 1% Eco, eldoLED 1% ECOdrive 0-10V, eldoLED 0.1% SOLOdrive 0-10V, ELV, TRIAC, and DALI protocol drivers. All of our standard 0-10V drivers are NEMA 410 compliant.

#### PoE

Depending on the PoE manufacturer selected, Lumenwerx will install the node in factory as either integral to the luminaire or as a remote module. These must be addressed and evaluated on a case-by-case basis.

#### **ELECTRICAL SECTION OPTIONS**

Electrical section options are available for fixtures specified as multi circuit (#MC). With MC, specify the total number of circuits (#), including any circuits required for optional electrical sections. A drawing is required to specify the layout. Please consult factory for custom configurations.

#### **Electrical sections**

Options include emergency-powered (#EC##), night light (#NL##), daylight (#DL##), and generator transfer device (#GTD##) sections. Specify the quantity (#), as well as the section length in inches (##).

Example 1: A 32' Direct fixture with two 8' emergency-powered sections on a second circuit.

Code: 2MC-2EC96

Example 2: A 24' Direct fixture with one 4' generator transfer device

Code: 1MC-1GTD48

#### **Battery**

Factory installed long life, high temperature, maintenance-free Lithium-Ion battery pack with self-test functionality, test switch and charge indicator. Minimum of 90 minutes operation, up to 1000 lumens per 4' (25°C) emergency lighting output and recharge time of 24 hours.

#### MOUNTING

Recessed fixtures can be mounted into exposed or concealed T-bar or tegular ceiling, as well as in ceilings with trim, trimless, or mud flange options.

#### **FINISH**

**Interior**: 95%, reflective matte powder coated white paint. **Exterior**: Matte white powder coating. Custom finishes are also available.

#### CONSTRUCTION

**Housing**: Extruded aluminum, up to 90% recycled content **Interior brackets**: Die-formed cold rolled sheet steel

Joining system: Die-cast zinc

Reflectors: Plastic Lens: Acrylic

Recessed flanges: Extruded aluminum, up to 90% recycled

content

End plate: Die-formed cold rolled sheet steel



#### WEIGHT

2.5 lb/ft - 1.13 kg/ft

#### CERTIFICATIONS

**ETL**: Rated for indoor dry/damp locations. Conforms to UL Standard 1598 and certified to CAN/CSA Standard C22.2 No. 250.0.

**Chicago Plenum**: City of Chicago Approved (CCEA) when specified with CP option.

IC rated: Suitable for direct contact with insulation

#### WARRANTY

Lumenwerx provides a five-year limited warranty on electrical and mechanical performance of the luminaires, including the LED boards, drivers, and auxiliary electronics. Lumenwerx will repair or replace defective luminaires or components at our discretion, provided they have been installed and operated in accordance with our specifications. Other limitations apply, please refer to the full warranty on our website.

